



# Care & Maintenance

It's not quite self-cleaning, but Wilsonart Flooring is one of the easiest to care for floors you'll ever own!

- Everyday cleaning: vacuum the floor or use a dry electrostatic cleaner to remove loose dirt and debris. Do **NOT** use Wet mops or Wipes containing oil, polishes, waxes or detergents such as Swiffer® Wet products.
- Deep cleaning: damp mop using two ounces of Wilsonart® Flooring Cleaner (Concentrate) diluted in a gallon of warm water and a cotton string or terrycloth mop. Never wash mop head in regular laundry detergent, soap or fabric softener (a residue can build up in the mop head and be transferred to the floor).
- Spot cleaning: Wilsonart Flooring Cleaner (Ready-To-Use Spray Bottle) may be sprayed directly on the floor and wiped with a flatbottom cotton/terrycloth mop.
- Preventive maintenance: Wilsonart Flooring recommends the use of felt pads on furniture legs and walk-off mats at outside entrances to prevent scratches and preserve the appearance of your floor.
- Recommended cleaning agents: Specially formulated Wilsonart Flooring Cleaner is recommended because it requires no rinsing and will not leave dull, cloudy or streaky residue behind. Should you experience cloudiness or streaking after using other cleaning products, a mixture of 2-4 ounces of ammonia diluted in a gallon of water may be used. **NOTE:** in extreme cases, Acetone may be used to remove the residue, followed by rinsing with 2-4 ounces Ammonia diluted in a gallon of water. Extra caution must be taken if Acetone is used on a beveled product as it will remove the color-match from the beveled edge.



For	Use
General cleaning	A terry cloth mop & 2 ounces of Wilsonart Flooring Cleaner (Concentrate) per gallon of warm water
Spot cleaning	Wilsonart Flooring Cleaner (Ready-To-Use) and a soft cloth
Juice, wine, dried foods	Warm water & Wilsonart Flooring Cleaner (Ready-To-Use)
Grease, crayon, asphalt, shoe and nail polish	Use Acetone to remove these items, followed by rinsing with 2-4 ounces Ammonia diluted in a gallon of water. Use extra caution when Acetone is used on a beveled product.
Candle wax, chewing gum	Allow to harden, then scrape with a dull blunt blade
<p><b>Important!</b> Abrasive cleansers and scouring pads should not be used because they can scratch and damage the surface of Wilsonart Flooring. Never wax, sand or apply lacquer to Wilsonart Flooring or use mechanical floor cleaning devices or detergents.</p>	

© 2009 Wilsonart International, Inc.